

# WH01X10343 Damper-Shock

## ATTENTION SERVICE TECH

Contents: Damper WH01X10343 1 each  
Damper Pin WH01X10261 1 each

1

### YOU MUST USE THE NEW DAMPER PIN WHEN YOU REPLACE THE DAMPER

The damper pin can be damaged when you remove it from the base. If damaged, the damper may not stay in place or it may generate noise.

---

2

### USE A 6" ADJUSTABLE CRESCENT WRENCH WHEN YOU INSTALL THE DAMPER INTO THE TUB BOTTOM

TWISTING THE BLACK PISTON BY HAND OR WITH THE WRONG TOOL MAY DAMAGE THE FIT OF THE PISTON INTO THE UPPER BUSHING, RESULTING IN LOUD SQUEEKING DURING THE WASH CYCLE.

1. To install the damper into tub bottom, align the arrowhead on the top of the upper bushing with the slot in the tub bottom.
2. Push the upper bushing upward by hand until the arrowhead is completely through the slot in the tub bottom.
3. Using a 6" adjustable crescent wrench, WITH a JAW OPENING of APPROX 7/8", clamp the wrench on to the upper bushing of the damper.

DO NOT CLAMP WITH A JAW OPENING OF 1 1/2" to prevent clamping the wrong part of the upper bushing, which will damage the bushing.

4. Twist the upper bushing COUNTERCLOCKWISE until the arrowhead is perpendicular to the slot and the locking tabs are in the square holes in the tub bottom.