

TECHNICAL INFORMATION BULLETIN

T8 U-BENT 800 SERIES

Ordering Information

Order code: 10482
 Description: FB32T8/30K/8/U6/RS/G13/STD ESV
 UPC: 69549104822
 Case quantity: 20



Performance Data

Initial lumens (lm): 2 550
 Mean lumens (lm): 2 220
 Nominal efficiency (lm/W): 80
 Wattage (W): 32
 Colour temperature (K): 3 000
 CRI: 85
 Average life (hrs): 20 000

¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

Lamp Characteristics

Shape: T8 U-Bent
 Base: Med Bipin
 Diameter: 1 in. (26 mm)
 Nominal length: 22 17/32 in. (572 mm)
 Starting method: Rapid Start
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Cathode guard: Yes
 Nominal lamp operating frequency (Hz): 60

² Minimum starting temperature (°C): -10


Benefits

One system Lamp/Ballast Warranty.
 Extended lamp warranty from 2 to 3 years and ballast warranty from 3 to 5 years.



² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T8 Instant Start ballast.

Dimensions



A Max Overall length
B Max Base face to top of lamp
C Max Leg spacing Center to center

FB32T8 23 in. 22.6 in. 6 in.
 584.2 mm 574.04 mm 152.4 mm

Spectral distribution

