

Rainfresh Drinking Water System  
Model – FC250



PERFORMANCE DATA SHEET

This system has been tested according to NSF/ANSI 42 for reduction of the substances listed below in Table I. The concentration of the indicated substances in the water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI.

Contaminant	Influent Challenge Concentration	Reduction Requirement	Average Reduction Efficiency
<i>Standard 42 – Aesthetic Effects.</i> Taste, Odour, Chlorine Reduction	2.0 mg/L ± 10%	≥ 50%	> 90%

TABLE- I

The standards referenced above evaluate performance for use with disinfected water.

All testing performed under standard laboratory conditions. Actual performance may vary.

Note: Contaminants reduced by this filter are not necessarily present in water. Individuals requiring water of specific microbiological purity should follow the advice of their doctor or local health unit.

**Technical Specifications**

- Replacement filter - Model CF2
- Rated filter life - 6 months or 1000 US gal (3785 Liters)
- Rated service flow - 0.75 US GPM (2.83 LPM)
- Inlet/Outlet connections - 3/4" FNPT
- Operating Temp - 4°C (39°F) min. to 38°C (100°F) max.
- Working Pressure - 20 psi (137 kPa) min. to 100 psi (689 kPa) max

**General Operation & Maintenance:** See product manual for maintenance instructions. User is responsible for general maintenance.

**Warranty –** Limited 5 year warranty. See product manual for details.

For replacement parts contact your nearest Rainfresh dealer.



Envirogard Products Limited  
446, Major Mackenzie Drive East, Richmond Hill,  
ON L4C 1J2, CANADA  
Tel: (905) 884 9388 Fax: (905) 884 3532.  
Web: [www.rainfresh.ca](http://www.rainfresh.ca)