

# ALR



**ALR** are halogen aluminium reflector lamps.

All models are fitted with a cover glass. They are a lightweight compact light source and are mainly used in display lighting, accent lighting, task lighting and elevator.

**ALR12  
(BA15d)**



MOL = 1 17/32 in. (39 mm)  
Dia. = 1 1/2 in. (38 mm)

**ALR18  
(BA15d)**



MOL = 2 1/4 in. (57 mm)  
Dia. = 2 1/4 in. (57 mm)

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour temp. (K)	Colour/Finish	Beam angle (°)	Beam Spread	CBCP (cd)	Initial lumens (lm)	Average life (hrs)	Case qty
------------	-------------	-----------	-----------	------	-----------	------------------	---------------	----------------	-------------	-----------	---------------------	--------------------	----------

## ALR12

11068	20ALR12/NSP6-GBD	GBD	20	BA15d	12	3 000	Clear	6	Narrow Spot	7 000	250	2 000	50
55061	20ALR12/F/SP/BA15d/12V/GBE STD	GBE	20	BA15d	12	3 000	Frost	18	Spot	1 000	1 500	2 000	20
55062	20ALR12/F/FL/BA15d/12V/GBF STD	GBF	20	BA15d	12	3 000	Frost	32	Flood	400	750	2 000	20

## ALR18

55010	H50ALR18/SP/CL/DC/12V/GBJ STD	GBJ	50	BA15d	12	3 000	Clear	10	Spot	13 900	N/A	2 000	25
55011	H50ALR18/NFL/F/DC/12V/GBK STD	GBK	50	BA15d	12	3 000	Frost	25	Narrow Flood	1 900	N/A	2 000	50



**J TYPE LAMPS** are double ended. STANDARD carries a vast selection of J lamps in T3 shape made of fine quality quartz glass.

**T3 - 79 mm**



**T3 - 119 mm**



**T3 - 256 mm**



Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour/Finish	Average life (hrs)	Initial lumens (lm)	MOL (in.) (mm)	Case qty
------------	-------------	-----------	-----------	------	-----------	---------------	--------------------	---------------------	----------------	----------

## T3 - 79 mm

55043	H60T3/79mm/CL/2M/R7S/130V/STD	-	60	R7s	130	Clear	2 000	880	3 1/8 79	12
57225	H75T3/79mm/2M/R7S/120V/STD	-	75	R7s	120	Clear	2 000	750	3 1/8 79	12

Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour/Finish	Average life (hrs)	Initial lumens (lm)	MOL (in.) (mm)	Case qty
<b>T3 79 mm (cont.)</b>										
51042	H75T3/79mm/R7S/130V/STD	-	75	R7s	130	Clear	2 000	792	3 1/8 79	12
55047	H75T3/79mm/CL/2M/R7S/130V/JPN/STD	-	75	R7s	130	Clear	2 000	1 150	3 1/8 79	12
57361	H100T3/79MM/2M/R7S/120V/STD	-	100	R7s	120	Clear	2 000	1 300	3 1/8 79	50
51043	H100T3/79mm/2M/R7S/130V/STD	-	100	R7s	130	Clear	2 000	1 300	3 1/8 79	12
57224	H150T3/79mm/2M/R7S/120V/STD	-	150	R7s	120	Clear	2 000	2 400	3 1/8 79	50
51075	H150T3/79mm/2M/R7S/130V/STD	-	150	R7s	130	Clear	2 000	2 400	3 1/8 79	50
51120	H200T3/79mm/2M/R7S/130V/STD	-	200	R7s	130	Clear	2 000	3 400	3 1/8 79	50
59350	300QT3/CL/130V/79MM/STD	EHP	300	R7s	130	Clear	2 000	5 400	3 1/8 79	50
<b>T3 119 mm</b>										
51086	H100T3/119mm/2M/R7S/130V/STD	-	100	R7s	130	Clear	2 000	1 300	4 11/16 119	50
59351	H150QT3/119mm/CL/2M/STD	-	150	R7s	120	Clear	2 000	2 250	4 11/16 119	50
50903	H150T3/119mm/2M/R7S/130V/STD	-	150	R7s	130	Clear	2 000	1 800	4 11/16 119	12
51044	H200T3/119mm/2M/R7S/130V/STD	-	200	R7s	130	Clear	2 000	3 400	4 11/16 119	50
51078	H300T3/119mm/CL/2M/R7S/120V/STD	EHM	300	R7s	120	Clear	2 000	5 950	4 11/16 119	12
15533	H300T3/2M/PB/130V	-	300	Pin Blade	130	Clear	2 000	5 400	4 11/16 119	50
51041	H300T3/119mm/CL/2M/R7S/130V/STD	FCL	300	R7s	130	Clear	2 000	5 950	4 11/16 119	12
51076	H500T3/119mm/CL/2M/R7S/120V/STD	DVS	500	R7s	120	Clear	2 000	10 500	4 11/16 119	12
51077	H500T3/119mm/CL/2M/R7S/130V/STD	-	500	R7s	130	Clear	2 000	10 500	4 11/16 119	12
51046	H1000T3/190mm/CL/2M/R7S/130V/STD	-	1 000	R7s	130	Clear	2 000	21 000	4 11/16 119	50
<b>T3 High voltage</b>										
59261	H300QT3/119mm/CL/2M/220V/STD	-	300	R7s	220	Clear	2 000	33 000	4 11/16 119	50
51047	H1000T3/190mm/CL/2M/R7S/240V/STD	DYD	1 000	R7s	240	Clear	2 000	21 000	7 15/32 190	12
51085	H1000T3/256mm/CL/2M/R7S/240V/STD	-	1 000	R7s	240	Clear	2 000	21 000	10 3/32 256	50
59262	H1500QT3/256mm/CL/2M/R7S/208V/STD	-	1 500	R7s	208	Clear	2 000	33 000	10 3/32 256	50
51049	H1500T3/256mm/CL/2M/R7S/240V/STD	-	1 500	R7s	240	Clear	2 000	26 400	10 3/32 256	50
59260	H1500QT3/256mm/CL/2M/277V/STD	-	1 500	R7s	277	Clear	2 000	33 000	10 3/32 256	50
<b>T3 Low voltage</b>										
55087	H100T3/79mm/CL/2M/R7S/12V/STD	-	100	R7s	12	Clear	2 000	2 900	3 1/8 79	10
55088	H150T3/79mm/2M/R7S/12V/STD	-	150	R7s	12	Clear	2 000	2 900	3 1/8 79	10
10154	H150T3/119mm/CL/2M/R7S/12V/STD	-	150	R7s	12	Clear	2 000	2 250	4 11/16 119	10
10318	H300T3/119mm/CL/2M/R7S/24V/STD	-	300	R7s	24	Clear	2 000	5 400	4 11/16 119	10
10319	H300T3/119mm/CL/2M/R7S/32V/STD	EHM	300	R7s	32	Clear	2 000	5 400	4 11/16 119	10
<b>T3 Infrared</b>										
55077	H375T3/221mm/CL/IR/5M/R7S/120V/STD	-	375	R7s	120	Clear	5 000	N/A	8 11/16 221	42
55070	H500T3/221MM/CL/IR/5M/R7S/120V/STD	-	500	R7s	120	Clear	5 000	N/A	8 11/16 221	42
55071	H500T3/224mm/CL/IR/5M/ML/120V/STD	-	500	Metal Leads	120	Clear	5 000	N/A	8 13/16 224	42
55073	H1000T3/303mm/CL/IR/5M/ML/240V/STD	-	1 000	Metal Leads	240	Clear	5 000	N/A	11 15/16 303	42
55072	H1000T3/351MM/CL/IR/5M/ML/240V/STD	-	1 000	Metal Leads	240	Clear	5 000	N/A	13 13/16 351	42
55074	H1600T3/503MM/CL/IR/5M/ML/240V/STD	-	1 600	Metal Leads	240	Clear	5 000	N/A	19 13/16 503	42
55075	H2500T3/732mm/CL/IR/5M/ML/480V/STD	-	2 500	Metal Leads	480	Clear	5 000	N/A	28 13/16 732	42
55076	H3800T3/1062MM/CL/IR/5M/ML/570V/STD	-	3 800	Metal Leads	570	Clear	5 000	N/A	41 13/16 1 062	36
<b>T3 Rough service</b>										
15491	500T3Q/CL/6 ROUGH SERVICE HAL	-	500	R7s	120	Clear	1 500	10 950	4 11/16 119	12