



MR11 AND MR16 LAMPS are available in a variety of wattages, voltages and beam spreads.

They are well suited to a variety of applications that require directional lighting of low to medium intensity.



**MR11
(G4)**



MOL = 1 3/8 in. (35 mm)
Dia. = 2 in. (51 mm)

**MR16
(GX5.3)**



MOL = 1 29/32 in. (45 mm)
Dia. = 2 in. (51 mm)

**MR16
(E26)**



MOL = 2 1/2 in. (55 mm)
Dia. = 2 in. (51 mm)

| Order code | Description | ANSI code | Watts (W) | Base | Volts (V) | Colour temp. (K) | Beam angle (°) | Beam spread | CBCP (cd) | Average life (hrs) | Initial lumens (lm) | Case qty |
|------------|-------------|-----------|-----------|------|-----------|------------------|----------------|-------------|-----------|--------------------|---------------------|----------|
|------------|-------------|-----------|-----------|------|-----------|------------------|----------------|-------------|-----------|--------------------|---------------------|----------|

MR11 Cover glass

| | | | | | | | | | | | | |
|-------|----------------------------------|--------|----|----|----|-------|----|--------------|-------|-------|-----|-----|
| 55093 | H5MR11/NSP/CG/2M/G4/6V/STD | - | 5 | G4 | 6 | 2 900 | 10 | Narrow Spot | 700 | 2 000 | 45 | 100 |
| 55094 | H10MR11/NSP/CG/2M/G4/6V/STD | - | 10 | G4 | 6 | 2 900 | 10 | Narrow Spot | 700 | 2 000 | 80 | 100 |
| 55054 | H5MR11/NSP/CG/2M/G4/12V/STD | - | 5 | G4 | 12 | 2 900 | 10 | Narrow Spot | 700 | 2 000 | 45 | 120 |
| 50900 | H20MR11/NFL/CG/2M/G4/12V/FTC STD | FTC/CG | 20 | G4 | 12 | 2 900 | 17 | Narrow Flood | 1 600 | 2 000 | 200 | 200 |
| 51050 | H20MR11/MFL/CG/2M/G4/12V/FTD STD | FTD/CG | 20 | G4 | 12 | 2 900 | 27 | Flood | 600 | 2 000 | 200 | 120 |
| 50901 | H35MR11/NFL/CG/2M/G4/12V/FTF STD | FTF/CG | 35 | G4 | 12 | 2 900 | 18 | Narrow Flood | 3 000 | 2 000 | 345 | 200 |
| 50899 | H35MR11/MFL/CG/2M/G4/12V/FTH STD | FTH/CG | 35 | G4 | 12 | 2 900 | 28 | Flood | 1 300 | 2 000 | 345 | 120 |

MR11 Open

| | | | | | | | | | | | | |
|-------|-------------------------------|-----|----|----|----|-------|----|--------------|-------|-------|-----|-----|
| 50894 | H20MR11/NSP/AX/G4/12V/FTB STD | FTB | 20 | G4 | 12 | 2 900 | 11 | Narrow Spot | 5 000 | 2 000 | 200 | 200 |
| 50895 | H20MR11/NFL/AX/G4/12V/FTC STD | FTC | 20 | G4 | 12 | 2 900 | 19 | Narrow Flood | 1 600 | 2 000 | 200 | 120 |
| 51054 | H20MR11/MFL/AX/G4/12V/FTD STD | FTD | 20 | G4 | 12 | 2 900 | 29 | Flood | 600 | 2 000 | 200 | 120 |
| 50897 | H35MR11/NFL/AX/G4/12V/FTF STD | FTF | 35 | G4 | 12 | 2 900 | 19 | Narrow Flood | 3 000 | 2 000 | 345 | 200 |
| 50898 | H35MR11/MFL/AX/G4/12V/FTH STD | FTH | 35 | G4 | 12 | 2 900 | 30 | Flood | 1 300 | 2 000 | 345 | 120 |

MR16 Cover glass

| | | | | | | | | | | | | |
|-------|------------------------------------|--------|----|-------|----|-------|----|-------|-------|-------|-----|-----|
| 51134 | H20MR16/FL/CG/4M/GX5.3/12V/BAB STD | BAB/CG | 20 | GX5.3 | 12 | 2 950 | 38 | Flood | 500 | 4 000 | 260 | 100 |
| 50892 | H35MR16/FL/CG/4M/GX5.3/12V/FMW STD | FMW/CG | 35 | GX5.3 | 12 | 3 000 | 38 | Flood | 1 000 | 4 000 | 530 | 100 |
| 50893 | H50MR16/FL/CG/4M/GX5.3/12V/EXN STD | EXN/CG | 50 | GX5.3 | 12 | 3 050 | 38 | Flood | 1 600 | 4 000 | 850 | 100 |

MR16 Cover glass - Line Voltage

| | | | | | | | | | | | | |
|--------|-------------------------------|---|----|-----|-----|-------|----|-------|-------|-------|-----|-----|
| 55570* | H35MR16/FL/CG/2M/E26/120V/STD | - | 35 | E26 | 120 | 2 800 | 38 | Flood | 800 | 2 000 | 240 | 100 |
| 57312* | H50MR16/FL/CG/2M/E27/120V/STD | - | 50 | E27 | 120 | 2 800 | 30 | Flood | 1 100 | 2 000 | 420 | 200 |
| 55569* | H50MR16/FL/CG/2M/E26/120V/STD | - | 50 | E26 | 120 | 2 800 | 38 | Flood | 1 100 | 2 000 | 420 | 100 |
| 59590* | H35MR16/FL/CG/E26/130V/STD | - | 35 | E26 | 130 | 2 800 | 38 | Flood | 800 | 2 500 | 180 | 100 |
| 59589* | H50MR16/FL/CG/E26/130V/STD | - | 50 | E26 | 130 | 2 800 | 38 | Flood | 1 100 | 2 500 | 315 | 100 |

MR16 Open

| | | | | | | | | | | | | |
|-------|----------------------------------|-----|----|-------|----|-------|----|--------------|-------|-------|-----|-----|
| 51066 | H20MR16/FL/4M/GX5.3/12V/BAB STD | BAB | 20 | GX5.3 | 12 | 2 950 | 36 | Flood | 500 | 4 000 | 260 | 100 |
| 50888 | H35MR16/FL/4M/GX5.3/12V/FMW STD | FMW | 35 | GX5.3 | 12 | 3 000 | 38 | Flood | 1 000 | 4 000 | 530 | 200 |
| 50889 | H50MR16/NSP/4M/GX5.3/12V/EXT STD | EXT | 50 | GX5.3 | 12 | 3 050 | 13 | Narrow Spot | 9 800 | 4 000 | 850 | 100 |
| 50890 | H50MR16/NFL/4M/GX5.3/12V/EXZ STD | EXZ | 50 | GX5.3 | 12 | 3 050 | 24 | Narrow Flood | 3 200 | 4 000 | 850 | 100 |
| 50891 | 50MR16/FL/4M/GX5.3/12V/EXN STD | EXN | 50 | GX5.3 | 12 | 3 050 | 38 | Flood | 1 600 | 4 000 | 850 | 100 |