

## Hubless - Totally Enclosed

Sleeve & Ball Bearing - Shaded Pole



**Fig. 1**  
R101  
R103  
R121  
R122  
R125  
R129  
R133  
R137  
R1211



**Fig. 2**  
R109  
R124  
R127  
R128



**Fig. 3**  
R101L  
R103L  
R114  
R119  
R120



**Fig. 4**  
R108



**Fig. 5**  
R123



**Fig. 6**  
R250

Motors

### 115 & 230 Volts

Part #	Amps.	H.P.	Spd/RPM	Voltage	Rotation	Body	Feature	Comment	Fig.
<b>R1211</b>	<b>0.30</b>	1/150	1/1550	115	C.W.	2.09	0.67" to hub face	5 Watt, Domestic Ref.	1
<b>R128</b>	<b>0.35</b>	1/135	1/1550	115	C.W.	2.09	3 Pt. Mtg., 3 Pin Plug	Coldstream	2
<b>R121</b>	<b>0.35</b>	1/60	1/1550	230	C.C.W.	2.50	3 pin Plug	Coldstream	1
<b>R122</b>	<b>0.35</b>	1/60	1/1550	230	C.W.	2.50	3 pin Plug	Foster, Coldstream	1
<b>R114</b>	<b>0.45</b>	1/125	1/1550	115	C.W.	2.09	Leads, 3 Point or Leg Mounting	General Replacement	3
<b>R123</b>	<b>0.50</b>	1/70	1/1550	115	C.W.	2.60	Two U brackets	Universal Cooler	5
<b>R250</b>	<b>0.50</b>	1/65	2/1500	115	C.C.W.	3.70	Two speed, Switch cord, plug	Selkirk	6
<b>R109</b>	<b>0.55</b>	1/135	1/1550	115	C.W.	2.00	2 Pin Plug	C.V.Hill	2
<b>R108</b>	<b>0.55</b>	1/95	1/1550	115	C.C.W.	2.00	One U Bracket, leads	Blanchard	4
<b>R119</b>	<b>0.55</b>	1/85	1/1550	115	C.C.W.	2.24	Leads, 3 Point or Leg Mounting	Foster	3
<b>R120</b>	<b>0.55</b>	1/85	1/1550	115	C.W.	2.24	Leads, 3 Point or Leg Mounting	Foster	3
<b>R137</b>	<b>0.59</b>	1/70	1/1550	115	C.W.	2.20	2 Pin Plug	Coldstream	1
<b>R129</b>	<b>0.65</b>	1/60	1/3000	115	C.C.W.	2.50	2 Pin plug	Hill Refrigeration	1
<b>R127</b>	<b>0.75</b>	1/80	1/1600	115	C.C.W.	2.09	Stud Mounting	Foster	2
<b>R125</b>	<b>0.80</b>	1/20	1/1500	230	C.C.W.	4.00	2 pin plug, Ball bearing	Dunham, Bush	1
<b>R101</b>	<b>0.90</b>	1/45	1/1550	115	C.W.	2.30	2 Pin Plug, Leg Mtg.	Hussman	1
<b>R101L</b>	<b>0.90</b>	1/45	1/1550	115	C.W.	2.30	2 Pin Plug	Hussman	3
<b>R103</b>	<b>0.90</b>	1/45	1/1550	115	C.C.W.	2.30	2 Pin Plug	Hussman	1
<b>R103L</b>	<b>0.90</b>	1/45	1/1550	115	C.C.W.	2.30	2 Pin Plug, Leg Mtg.	Hussman	3
<b>R133</b>	<b>1.00</b>	1/40	2/1550	115	C.C.W.	2.60	Two speed	Mark Hot	1
<b>R124</b>	<b>1.55</b>	1/20	1/1550	115	C.C.W.	4.00	2 pin plug, Ball bearing	Dunham Bush	2

Rotation determined opposite shaft end  
Double shaft determined at lead end

Shaft length measured from hub  
face to shaft end