

Open Construction - Single Shaft

Sleeve & Ball Bearing - Shaded Pole & P.S.C.



Fig. 1
R302



Fig. 2
R304 R317
R308 R320
R309 R325
R311 R395
R315



Fig. 3
R306
R322
R410



Fig. 4
R337
R90015
R90014



Fig. 5
R370
R371
R91125



Fig. 6
R130
R326




Fig. 7
R480



Fig. 8
R90575

1550 RPM-115, 208, 230 volts

Part #	Amps	Volts	H.P.	Rot.	Shaft	Body	Feature	Comment	Fig.
R302	0.20	230	1/100	C.W.	2.0"x1/4"	2.25	4 studs rear	Camco, FPE	1
R325	0.33	115	1/125	C.C.W.	2.3"x1/4"	2.09	16" leads shaft end	W.C.Woods	2
R410	0.35	115	1/130	C.W.	2.0"x5/16"	2.75	L.K.Fitting-int.fan	Enterprise Fdry.	3
R371	0.38	230	1/20	C.W.	2.6"x5/16"	4.00	PSC/Cap. inc., Plug, Ball Bearing	Keeprite 501909, 501525	5
R337	0.40	115	1/200	C.C.W.	1.5"x1/4"	2.30	2 speed motor	Hunter 902538	4
R326	0.40	115	1/110	C.W.	1.4"x1/4"	2.09	U Brk. 35" leads	Blanchard E1001,2,3	6
R311	0.47	115	1/100	C.W.	1.2"x5/16"	2.09	Hex Hubs, cord & plug	Nutone 81176, 23405	2
R320	0.47	115	1/100	C.W.	1.3"x1/4"	2.10	18" leads	Moyer & Diebel	2
R91125	0.50	208/230	1/12	CW	2.63"x5/16"	3.66	PSC/Cap.Inc	9720A, D1125, 41125	5
R315	0.53	115	1/90	C.C.W.	1.2"x1/4"	2.09	Hex Hubs, cord & plug	Nutone 82598, 82599, 65070	2
R317	0.60	115	1/65	C.C.W.	1.6"x1/4"	2.30	Hex hubs	Nutone 65072	2
R306	0.65	115	1/60	C.W.	1.2"x1/4"	2.92	Internal Fan / oilers	Coleman	3
R309	0.68	115	1/70	C.W.	2.4"x1/4"	2.00	12.5" leads	Gen. Replacement	2
R90015	0.70	115	1/70	CW	2.24"x1/4"	2.14	4 Studs front & rear	15, D121, 40121, 3M539	4
R90014	0.70	115	1/70	CCW	2.24"x1/4"	2.14	4 Studs front & rear	14, D120, 40120, 3M538	4
R308	0.70	115	1/70	C.C.W.	2.3"x1/4"	2.00	12.5" leads	Gen. Replacement	2
R370	0.75	115	1/20	C.W.	2.8"x5/16"	4.00	Cap.inc.Plug, Ball Bearing	Keeprite 501895, 505124	5
R322	0.80	115	1/60	C.W.	1.3"x1/4"	2.00	Cord & plug	Broan 30080111, 112	3
R480	0.80	208/230	1/30	C.C.W.	2.4"x3/8"	4.00	4 Lugs Front and Back	Chromalox/Westcan	7
R130	0.80	230	1/25	C.W.	1.5"x5/16"	2.72	Single U Brk, 35" leads	Blanchard0.	6
R395	0.81	208/230	1/20	C.W.	2.5"x5/16"	2.75	Cord & plug	Larkin 2531195	2
R90575	0.89	230	1/20	CW	2.48"x5/16"	2.75	2 Pin plug	575, D1103, 41195,	8
R304	0.89	115	1/40	C.W.	1.5"x1/4"	2.50	LK fitting.	Nutone	2

3.3" Motors continued on next page.

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end