


Single Speed Belted Fan Motors



**Ball Bearing
Commercial Ventilation!
BF-4707 (1/3 HP)
BF-4709 (1/2 HP)**



Motors

Single Speed

Part #	HP	Volts	Amps	S.F.	RPM	Rotation	A Dim.	Bearing	Shaft
BF-4701	1/4	115	5.8	1.35	1/1725	Revers.	6.25"	Sleeve	1/2"x1.5"
BF-4706	1/3	115	7.3	1.35	1/1725	Revers.	6.25"	Sleeve	1/2"x1.5"
BF-4707	1/3	115	7.3	1.35	1/1725	Revers.	6.25"	Ball	1/2"x1.5"
BF-4708	1/2	115	9.9	1.25	1/1725	Revers.	6.75"	Sleeve	1/2"x1.5"
BF-4709	1/2	115	9.9	1.25	1/1725	Revers.	6.75"	Ball	1/2"x1.5"

Features


- 48 Frame
- 5.5" Diameter
- Open Drip Proof
- Resilient Ring & Base Included
- 60 Hz
- Ball & Sleeve Bearing
- Shaft: 1/2" x 1.5" W/ Flat
- Reversible
- Split Phase
- 45°C (113°F) Ambient
- Insulation Class B
- Thermally Protected

Cross Reference

Rotom	AO Smith	Emerson	Fasco	GE	Marathon	UE	Rotom
BF-4701	GF2024	840CV	D6002	4701, H701	D127, B206, B303	-	R840
BF-4706	GF2034	841CV	-	4706, H711	D143, B207	-	R841
BF-4707	GF2034B	2888	D6004	4682, H165	B305, B703	906, 921, 922	R2888
BF-4708	GF2054	1542C	-	4708	D162, B208	-	R5794
BF-4709	-	2887	D6006	4684, H703	B307	-	R2887

Two Speed Belted Fan

- Reversible
- Shaded Pole & Split Phase
- Resilient Ring & Base Included



Part #	HP	Volts	Amps	S.F.	RPM	Type	C Dim.	Fr.	Bearing	Shaft
R5793	1/3	115	6.7	1.35	2/1725	SPLT/ ODP	8.30"	56Z	Sleeve	1/2"x1.6"
R5794	1/2	115	7.20	1.25	2/1725	SP/ Open.	9.9"	48/56	Sleeve	1.5"x1/2"

*5/8" Thru-bolts shaft end.

Part #	Comment
R5793	Emerson 5793, K5793, U.E. 849, G.E. 5J765GS
R5794	B200, D149, D162, S121, 1542, 7J403AS, 7J403AX

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end

www.rotom.ca