

## Features

- 1.5 pole (1 pole with shunt) 30 & 40 amp to 2 pole 20, 25, 30 & 40 amp.
- Features lug, spade terminals and protective covers
- Compact size
- Universal galvanized mounting plates
- ARI 780/790 standards
- Brass/copper terminals
- Quick connect and screw terminals on coil.
- Snap on auxiliary contacts available
- cURus approved



## 1 Pole with Shunt and 2 Pole Models

Part #	Poles	Full Load Amps.	Coil Voltage 50/60	Locked Rotor Amps			Resistive Amps.	Termination	Furnas #
				240V	480V	600V			
<b>DP-1P30A24</b>	1.5	30	24	180	150	120	40	Screw Type	45EG10AJA
<b>DP-1P30A120</b>	1.5	30	120	180	150	120	40		45EG10AFA
<b>DP-1P30A240</b>	1.5	30	208/240	180	150	120	40		45EG10AGA
<b>DP-1P40A24</b>	1.5	40	24	240	200	160	50	Box Lug	45GG10AJAL, 45FG10AJA, 45GG10AJA
<b>DP-1P40A120</b>	1.5	40	120	240	200	160	50		45GG10AFAL, 45FG10AFA, 45GG10AFA
<b>DP-1P40A240</b>	1.5	40	208/240	240	200	160	50		45GG10AGAL, 45FG10AGA, 45GG10AGA
<b>DP-2P20A24</b>	2	20	24	120	100	80	30	Box Lug	45CG20AJ
<b>DP-2P20A120</b>	2	20	120	120	100	80	30		45CG20AF
<b>DP-2P20A240</b>	2	20	208/240	120	100	80	30		45CG20AG
<b>DP-2P25A24</b>	2	25	24	150	125	100	35	Box Lug	45DG20AJ
<b>DP-2P25A120</b>	2	25	120	150	125	100	35		45DG20AF
<b>DP-2P25A240</b>	2	25	208/240	150	125	100	35		45DG20AG
<b>DP-2P30A24</b>	2	30	24	180	150	120	40	Screw Type	45EG20AJ
<b>DP-2P30A120</b>	2	30	120	180	150	120	40		45EG20AF
<b>DP-2P30A240</b>	2	30	208/240	180	150	120	40		45EG20AG
<b>DP-2P40A24</b>	2	40	24	240	200	160	50	Box Lug	45GG20AJL
<b>DP-2P40A120</b>	2	40	120	240	200	160	50		45GG20AFL
<b>DP-2P40A240</b>	2	40	208/240	240	200	160	50		45GG20AGL