

# TECHNICAL DATA SHEET


## APPLIANCE CONNECTOR - STATIONARY (ACS)

### Applications:

Gas appliance Connectors for a wide variety of gas applications.

### STAINLESS STEEL GAS CONNECTORS (Stationary) FOR DOMESTIC APPLIANCES

• ANSI Z21.24 - C.S.A. 6.10 "Connectors for Gas Appliances"



Yellow Coated

ACS Series Gas Appliance Connector BTU Capacity / Hr. (Flow capacities are based 0.64 specific gravity @ 0.5" w.c. pressure drop)									
I.D. (IN.)	Series	12"	18"	24"	30"	36"	48"	60"	72"
1/4"	ACS-250	48,000	43,600	40,000	36,400	33,400	28,300	24,900	23,100
3/8"	ACS-375	102,000	93,100	85,000	77,100	71,000	60,500	53,200	49,100
1/2"	ACS-50	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000

50, 250, 375 SERIES  
AVAILABLE WITHOUT  
COATING



250 & 375 SERIES  
AVAILABLE WITH BLACK  
COATING - WHISTLE FREE



Our New Appliance Connector Rack holds up to 32 assemblies ask about it.



The above stationary connectors may be used with: Natural, manufactured, mixed liquefied petroleum gases, and LP gas-air mixtures. The added protection of stainless steel is especially useful in areas where the natural gas has a high sulfur content.  
Developed for use in: Household Kitchens • Utility Rooms • Laundry Rooms • Pulse Combustion Furnaces (AGAL) • Forced Air Heating Units • Rooftop HVAC Units • Campfire Log Sets • Fireplaces.

**TO BE INSTALLED BY LICENSED GAS FITTERS ONLY.**